



Application :

This STREAM SELECTOR UNIT is based on a popular 8-bit Microcontroller. The system is designed to control the timing of stream selection of up to eight streams system using its timer and relay outputs. It also generates Sample and Hold analog outputs for each channel.

Specifications:

- No. of Streams: Up to 8
- Operating Voltage: 110-230 VAC +/- 10%, 1 Phase, 50 Hz Nominal
- Key board: 12 keys keypad
- Display: 7 digit 7-Segment, 0.56" Green/Red LED
 - 20 Character x 4 Line LCD
- Display: 16/32 Discrete LEDs for process status Indication
- Relays: Stream selection: Up to 8 Relays 2 C/O type
- Stream selection logic: time based or external input triggered
- Alarm Relays (Optional):
 - Up to 8 Relays 1 C/O type
 - Common Alarm (Optional):
 - 1 Relay 1 C/O type
 - Contact rating: 2A/250 AC, Resistive for each relay
- Analog Input:
 - 1 channel, 4 to 20 mA
- Analog Output: Up to 16 Channels, 4 to 20 mA
 - One Output or Dual Output per stream
- Dimension:
 - Outer: 270 (W) x 133.5 (H) x 260 (D)
 - Cutout: 228 (W) x 133.5 (H)
- Weight: 6 Kgs
- Enclosure: General purpose, Made up of Aluminum, Panel Mount

Mfg & Marketed by
Steam Equipments Pvt Ltd
 No-44, Tiny Industrial Estate
 Kondhwa Budurk, Pune – 411 048
 Phone / Fax : +91 (20) 2693 0908, 26930959
 Email : sales@steamequipments.com
<http://www.steamequipments.com>

Representatives
India : Pune, Mumbai, Delhi, Bangalore,
 Hyderabad, Chandigarh, Goa, Surat,
 Korba, Jemshedpur, Nagpur
Overseas : Dubai (UAE), Oman, Saudi
 Arabia, Indonesia, Malaysia, Hongkong,
 United Kingdom, USA, Egypt